



## Synergy 21 Tira LED Flex 24V/72W RGB+ Super blanco cálido



kwh/1000h:	90,00
Lúmenes:	1500
Vatio:	90,0
Vida útil nominal:	35000 Std.
Ciclos de conmutación:	50000
Temperatura ambiente óptima:	25 °C



- CCT: 2600K
- Voltaje: DC24V/72W/3A
- Número de Leds: 300 SMD5050
- Polo positivo
- Dimensiones: 5000 x 12 x 2,2
- Se puede cortar cara 6 SMD (10 cm)
- Compatible con controlador PortaLuce u otro controlador RGB-Blanco
- (RF, DMX, etc.)

- Tenga en cuenta que las tiras de Synergy 21 deben funcionar a una temperatura no superior a los 40°

## Atributos

Atributo	Valor
Abstrahlwinkel:	120
Ampere:	3.80
CC oder CV:	CV

Atributo	Valor
Dimmbar:	abhängig vom Netzteil
EPREL_ANTI_GLARE_SHIELD:	false
EPREL_BEAM_ANGLE:	Not applicable
EPREL_BEAM_ANGLE_CORRESPONDENCE:	SPHERE_360
EPREL_CHROMATICITY_COORD_X:	0.471
EPREL_CHROMATICITY_COORD_Y:	0.411
EPREL_CLAIM_EQUIVALENT_POWER:	false
EPREL_COLOUR_RENDERING_INDEX:	81
EPREL_COLOUR_TUNEABLE_LIGHT_SOURCE:	false
EPREL_CONNECTED_LIGHT_SOURCE:	false
EPREL_CORRELATED_COLOUR_TEMP_TYPE:	RANGE
EPREL_DIMENSION_DEPTH:	1000
EPREL_DIMENSION_HEIGHT:	2
EPREL_DIMENSION_WIDTH:	10
EPREL_DIMMABLE:	SPECIFIC
EPREL_DIRECTIONAL:	NDLS
EPREL_ENERGY_CLASS:	F
EPREL_ENERGY_CONS_ON_MODE:	5
EPREL_ENVELOPE:	NO
EPREL_EQUIVALENT_POWER:	Not applicable
EPREL_HIGH_LUMINANCE_LIGHT_SOURCE:	false
EPREL_LIGHTING_TECHNOLOGY:	LED
EPREL_LUMEN_MAINTENANCE_FACTOR:	0.96
EPREL_LUMINOUS_FLUX:	538
EPREL_MAINS:	NMLS
EPREL_MAX_BEAM_ANGLE:	Not applicable
EPREL_MAX_COLOUR_RENDERING_INDEX:	85
EPREL_MIN_BEAM_ANGLE:	Not applicable
EPREL_MIN_COLOUR_RENDERING_INDEX:	80
EPREL_POWER_ON_MODE:	5.0
EPREL_POWER_STANDBY:	0.00

Atributo	Valor
EPREL_R9_COLOUR_RENDERING_INDEX:	0.7
EPREL_REGISTRANT_NATURE:	MANUFACTURER
EPREL_REPLACEMENT_CLAIM:	Not applicable
EPREL_SURVIVAL_FACTOR:	1.00
Länge:	5
LED Strip Klebeband:	ja
LED Strip Breite:	10
LED Strip Höhe:	2.20
LED Strip Klebeband:	ja
LED Strip kürzbar:	100
LED Strip Länge:	5000
Lichtfarbe:	RGB-W
Lichtfarbe Name:	RGB-W
Schutzklasse:	IP20
Volt:	24
Peso:	0.1 Kg

## Imágenes adicionales



## Accesorios

Número de artículo	Denominación
135731	Synergy 21 LED Controller 3653 LED RGB-WW (RGB-CCT) Master Set
81069	Synergy 21 Enchufe DC con borne de tornillo
81068	Synergy 21 Conector DC con borne de tornillo
81741	Synergy 21 Clip fijación de silicona para tiras LED, Pack de
125198	Mean Well LPV-150-24 Alimentación 24V/150W IP67
151666	Synergy 21 LED Controller EOS 05 5-Kanal Controller RGB-WW (RGB-CCT)
151667	Synergy 21 LED Controller EOS 05 5-Kanal Handsender RGB-WW (RGB-CCT)
126644	Synergy 21 LED Controller EOS 05 Wandtaster AC RGB-W
101873	Synergy 21 Controlador RF RGB-Blanco, Emisor
178378	Synergy 21 LED Controller EOS 07 DALI DT8 RGB-WW (CCT)
178440	Synergy 21 Controlador EOS 10 ZigBee, 5 canales, RGB-WW
178421	Synergy 21 LED Controller EOS 10 ZigBee CC Controller+Netzteil 4-Kanal 75W RGB-W
178432	Synergy 21 LED Controller EOS 10 ZigBee CV Controller+Netzteil 4-Kanal 100W RGB-W 12V
178433	Synergy 21 LED Controller EOS 10 ZigBee CV Controller+Netzteil 4-Kanal 100W RGB-W 24V
181495	Synergy 21 LED Controller RGB-W DC12/24V *Milight/Miboxer*
149147	Synergy 21 LED Controller RGB-WW (RGB-CCT) DC12/24V *Milight/Miboxer*
181496	Synergy 21 LED Controller RGB-WW (RGB-CCT) DC12/24V *Milight/Miboxer*
178064	Synergy 21 LED Controller RGB-WW (RGB-CCT) DC12/24V Strip/Panel 5in1 *Milight/Miboxer*
180638	Synergy 21 LED Controller RGB-WW (RGB-CCT) DC12/24V WiFi 5in1 *Milight/Miboxer* Alexa Serie
159228	Synergy 21 Controlador + Alimentación 24V/100W RGB-WW
183258	Shelly RGBW2 Relé Wi-Fi