



NOTE:

1. Electrical test:
  - (1). 100% open short & miss wire test;
  - (2). Insulation resistance: DC 300V 10M ohm;
  - (3). Contactor resistance: 10 ohm;
  - (4). Dielectric strength: 150V AC/Sec, 1mA.
  - (5). Computer + HDTV TEST 3840\*2160@60Hz 4:4:4 8bit
2. RoHS3.0 AND REACH COMPLIANT
3. PRINT WORD: High Speed HDMI® Cable with Ethernet
4. PACKING: 1PC/SYNERGY 21 Bag C Bag+LABLE 1, inner carton+outer carton+LABLE 3

MATERIAL LIST:

④	OUTER MOLD	PVC 88A Black	2	
③	INNER MOLD	LD-PE	2	
②	HDMI Connector	19P A/Male The Pin Gold Plated, The Shell Gold Plating	2	
①	CABLE	(24AWG BC*1P+E+AM)*5P+28AWG BC*4C+AEB E:28AWG BC PVC/Black OD 9.5±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK

ITEM NO	LENGTH	PACKING
S215384V2	10000±150mm	SYNERGY 21 Bag

SYNERGY 21							
CUSTOMER	AN		ITEM NO.	SEE THE CHART			
PRODUCT NAME	HDMI2.0b 19P AM-AM WITH ETHERNET 26AWG		manufacture country:	CHINA	UNIT	MM	
DRAWNBY	CHECKBY	APPOBY	DATE				
SYNERGY 21	SYNERGY 21	SYNERGY 21	2019-09-26				

		change the model	2023-10-16	A2
		25+28AWG to 24+28AWG	2019-10-08	A1
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.