



PIN OUT



NOTE:

1. Fluke Channel Test ISO 11801 channel Class Ea
2. RoHS 3.0 AND REACH compliant
3. Electrical test: 100% open short & miss wire test;
4. OPERATING TEMPERATURE: -20°C ~ 75°C
STORAGE TEMPERATURE: -10°C ~ 60°C
5. Print word: CAT6A U/FTP Patch cord with CAT7 RAW Cable 4x2x32AWG/7
TPE-LSZH ISO11801 & EN50173 & ANSI/TIA568C.2 www.synergy21.de **CE**
6. Raw cable is Cat7 up to 600Mhz
7. Packing: 1pc/synergy 21 bag+label

MATERIAL LIST

| | | | | |
|---|-----------|---|---|--|
| ③ | CABLE | CAT. 7 U/FTP (32AWG BC*1P+AL-FOIL)*4+DRAIN+ JACKET: TPE-LSZH, OD: 3.8 ± 0.2mm | 1 | |
| ② | Over mold | 48P PVC | 2 | |
| ① | Plug | RJ45 8P8C Shielded Plug, PIN GOLD PLATED 3u", TRANSPARENT YELLOW | 2 | |

| NO. | PARTS NAME | SPECIFICATION STANDARD | QT' Y | REMARK |
|-----|------------|-------------------------------|------------|--------|
| | Hasia | Add the meter scale | 2022-12-26 | A1 |
| | | NEW | 2022-05-13 | A0 |
| BY | CHK | REVISION RECORD MODIFICATIONS | DATE | REV. |

SYNERGY21

| | | | |
|--------------|---|----------------------|------------|
| CUSTOMER | | ITEM NO. | |
| PRODUCT NAME | Super slim CAT6A U/FTP Patch cord With CAT7 RAW Cable | manufacture country: | CHINA |
| DRAWNBY | CHECKBY | APPOBY | UNIT |
| SYNERGY21 | SYNERGY21 | SYNERGY21 | MM |
| | | DATE | 2022-05-13 |

